



Reloading Data Center

338 Norma Magnum

Your search returned **52 loads items**

Twist: 1:8.000"

Barrel Length: 24.000"

Trim Length: 2.482"

Bullet: 250 GR. BAR LRX

Diameter: 0.338"

Case: NORMA

Primer: Federal 215M, Large Rifle Magnum Match

Manufacturer	Powder	C.O.L.	Starting Load			Maximum Load		
			Grs.	Vel. (ft/s)	Pressure	Grs.	Vel. (ft/s)	Pressure
Ramshot	LRT	3.610"	88.2	2,499	44,500 PSI	98.0	2,785	58,000 PSI
Hodgdon	H50BMG	3.610"	86.7	2,478	47,400 PSI	96.3	2,713	58,000 PSI
Winchester	StaBALL HD	3.610"	82.1	2,495	47,900 PSI	91.2	2,733	61,000 PSI
Ramshot	Magnum	3.610"	81.8	2,535	48,100 PSI	90.8	2,795	61,100 PSI
Accurate	Magpro	3.610"	79.4	2,515	48,100 PSI	88.2	2,765	60,400 PSI
Hodgdon	Retumbo	3.610"	78.8	2,509	46,800 PSI	87.6	2,762	59,800 PSI
Hodgdon	H1000	3.610"	78.4	2,555	49,300 PSI	87.1	2,780	61,300 PSI
IMR	IMR 7828 SSC	3.610"	74.2	2,495	48,100 PSI	82.4	2,715	60,000 PSI

Bullet: 250 GR. SIE HPBT	Diameter: 0.338"	Case: NORMA	Primer: Federal 215M, Large Rifle Magnum Match
--------------------------	------------------	-------------	--

Manufacturer	Powder	C.O.L.	Starting Load			Maximum Load		
			Grs.	Vel. (ft/s)	Pressure	Grs.	Vel. (ft/s)	Pressure
Ramshot	LRT	3.575"	90.8	2,635	47,300 PSI	100.9	2,901	59,700 PSI
Winchester	StaBALL HD	3.575"	85.4	2,567	46,400 PSI	94.9	2,822	60,800 PSI
Ramshot	Magnum	3.575"	83.6	2,641	47,100 PSI	92.9	2,872	61,100 PSI
Hodgdon	Retumbo	3.575"	82.2	2,578	45,900 PSI	91.3	2,848	59,500 PSI
Hodgdon	H1000	3.575"	80.5	2,585	46,000 PSI	89.5	2,841	60,300 PSI
Accurate	Magpro	3.575"	79.7	2,572	46,200 PSI	88.5	2,818	60,100 PSI
IMR	IMR 7828 SSC	3.575"	77.2	2,578	49,600 PSI	85.8	2,821	61,200 PSI
Hodgdon	H4831	3.575"	75.8	2,444	48,900 PSI	84.3	2,776	60,000 PSI

Bullet: 270 GR. HDY ELD-X	Diameter: 0.338"	Case: NORMA	Primer: Federal 215M, Large Rifle Magnum Match
---------------------------	------------------	-------------	--

Manufacturer	Powder	C.O.L.	Starting Load			Maximum Load		
			Grs.	Vel. (ft/s)	Pressure	Grs.	Vel. (ft/s)	Pressure
Ramshot	LRT	3.620"	89.5	2,539	46,300 PSI	99.4	2,814	59,500 PSI
Winchester	StaBALL HD	3.620"	83.1	2,447	45,300 PSI	92.4	2,716	59,700 PSI
Ramshot	Magnum	3.620"	81.7	2,495	46,200 PSI	90.8	2,758	60,900 PSI

Hodgdon	Retumbo	3.620"	81.0	2,505	46,600 PSI	90.0	2,775	60,200 PSI
Accurate	Magpro	3.620"	79.3	2,515	47,200 PSI	88.1	2,763	61,000 PSI
Hodgdon	H1000	3.620"	78.7	2,534	48,900 PSI	87.5	2,748	60,500 PSI
IMR	IMR 7828 SSC	3.620"	75.1	2,485	48,700 PSI	83.5	2,718	60,900 PSI

Bullet: 280 GR. BAR LRX	Diameter: 0.338"	Case: NORMA	Primer: Federal 215M, Large Rifle Magnum Match
-------------------------	------------------	-------------	--

Manufacturer	Powder	C.O.L.	Starting Load			Maximum Load		
			Grs.	Vel. (ft/s)	Pressure	Grs.	Vel. (ft/s)	Pressure
Hodgdon	US 869	3.610"	88.6	2,477	45,900 PSI	98.4	2,701	58,000 PSI
Ramshot	LRT	3.610"	84.9	2,428	46,400 PSI	94.4	2,688	60,100 PSI
Hodgdon	H50BMG	3.610"	82.2	2,341	46,800 PSI	91.3	2,573	59,000 PSI
Winchester	StaBALL HD	3.610"	76.5	2,304	49,200 PSI	85.0	2,509	61,200 PSI
Ramshot	Magnum	3.610"	74.6	2,398	50,500 PSI	82.8	2,606	61,000 PSI
Hodgdon	Retumbo	3.610"	74.2	2,373	48,200 PSI	82.4	2,570	60,100 PSI
Hodgdon	H1000	3.610"	73.1	2,376	48,900 PSI	81.2	2,591	61,100 PSI
IMR	IMR 7828 SSC	3.610"	70.0	2,341	49,500 PSI	77.7	2,558	61,500 PSI

Bullet: 285 GR. HDY ELD-M	Diameter: 0.338"	Case: NORMA	Primer: Federal 215M, Large Rifle Magnum Match
---------------------------	------------------	-------------	--

			Starting Load			Maximum Load		
Manufacturer	Powder	C.O.L.	Grs.	Vel. (ft/s)	Pressure	Grs.	Vel. (ft/s)	Pressure
Ramshot	LRT	3.630"	87.2	2,498	45,200 PSI	96.9	2,775	60,000 PSI
Hodgdon	H50BMG	3.630"	85.9	2,374	44,800 PSI	95.4	2,627	57,000 PSI
Winchester	StaBALL HD	3.630"	80.8	2,407	45,900 PSI	89.8	2,673	60,200 PSI
Ramshot	Magnum	3.630"	79.4	2,462	47,600 PSI	88.2	2,705	60,400 PSI
Hodgdon	Retumbo	3.630"	78.8	2,422	44,400 PSI	87.5	2,691	59,900 PSI
Hodgdon	H1000	3.630"	76.8	2,424	45,000 PSI	85.4	2,676	60,000 PSI
IMR	IMR 7828 SSC	3.630"	74.2	2,407	46,600 PSI	82.4	2,664	61,000 PSI

Bullet: 300 GR. BER HYBRID	Diameter: 0.338"	Case: NORMA	Primer: Federal 215M, Large Rifle Magnum Match
----------------------------	------------------	-------------	--

			Starting Load			Maximum Load		
Manufacturer	Powder	C.O.L.	Grs.	Vel. (ft/s)	Pressure	Grs.	Vel. (ft/s)	Pressure
Hodgdon	US 869	3.690"	91.7	2,486	45,400 PSI	101.9	2,734	58,000 PSI
Ramshot	LRT	3.690"	86.0	2,450	46,700 PSI	95.6	2,715	60,400 PSI
Hodgdon	H50BMG	3.690"	83.9	2,295	43,400 PSI	93.2	2,583	59,000 PSI
Winchester	StaBALL HD	3.690"	83.0	2,483	53,400 PSI	87.4	2,607	60,900 PSI
Hodgdon	Retumbo	3.690"	77.0	2,379	45,200 PSI	85.5	2,627	61,000 PSI
Hodgdon	H1000	3.690"	74.0	2,390	48,700 PSI	82.3	2,595	61,200 PSI

Bullet: 300 GR. SIE HPBT	Diameter: 0.338"	Case: NORMA	Primer: Federal 215M, Large Rifle Magnum Match
--------------------------	------------------	-------------	--

Manufacturer	Powder	C.O.L.	Starting Load			Maximum Load		
			Grs.	Vel. (ft/s)	Pressure	Grs.	Vel. (ft/s)	Pressure
Hodgdon	US 869	3.600"	91.6	2,391	41,200 PSI	101.8	2,674	55,000 PSI
Ramshot	LRT	3.600"	85.7	2,455	48,500 PSI	95.2	2,709	61,000 PSI
Hodgdon	H50BMG	3.600"	85.4	2,315	44,100 PSI	94.9	2,586	59,000 PSI
Winchester	StaBALL HD	3.600"	79.8	2,345	45,500 PSI	88.7	2,609	60,000 PSI
Hodgdon	Retumbo	3.600"	78.4	2,367	43,700 PSI	87.1	2,649	61,200 PSI
Ramshot	Magnum	3.600"	77.3	2,359	46,900 PSI	85.9	2,599	61,100 PSI
Hodgdon	H1000	3.600"	75.9	2,389	48,100 PSI	84.4	2,608	61,000 PSI
IMR	IMR 7828 SSC	3.600"	71.6	2,364	48,700 PSI	79.5	2,565	60,500 PSI